NASA/TM-2000-209891, Vol. 14



Technical Report Series on the Boreal Ecosystem-Atmosphere Study (BOREAS)

Forrest G. Hall and Jeffrey A. Newcomer, Editors

Volume 14 BOREAS AFM-06 Mean Wind Profile Data

J. Wilczak

National Aeronautics and Space Administration

Goddard Space Flight Center Greenbelt, Maryland 20771

The NASA STI Program Office ... in Profile

Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA Scientific and Technical Information (STI) Program Office plays a key part in helping NASA maintain this important role.

The NASA STI Program Office is operated by Langley Research Center, the lead center for NASA's scientific and technical information. The NASA STI Program Office provides access to the NASA STI Database, the largest collection of aeronautical and space science STI in the world. The Program Office is also NASA's institutional mechanism for disseminating the results of its research and development activities. These results are published by NASA in the NASA STI Report Series, which includes the following report types:

- TECHNICAL PUBLICATION. Reports of completed research or a major significant phase of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA's counterpart of peer-reviewed formal professional papers but has less stringent limitations on manuscript length and extent of graphic presentations.
- TECHNICAL MEMORANDUM. Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
- CONTRACTOR REPORT. Scientific and technical findings by NASA-sponsored contractors and grantees.

- CONFERENCE PUBLICATION. Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or cosponsored by NASA.
- SPECIAL PUBLICATION. Scientific, technical, or historical information from NASA programs, projects, and mission, often concerned with subjects having substantial public interest.
- TECHNICAL TRANSLATION.
 English-language translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services that complement the STI Program Office's diverse offerings include creating custom thesauri, building customized databases, organizing and publishing research results . . . even providing videos.

For more information about the NASA STI Program Office, see the following:

- Access the NASA STI Program Home Page at http://www.sti.nasa.gov/STI-homepage.html
- E-mail your question via the Internet to help@sti.nasa.gov
- Fax your question to the NASA Access Help Desk at (301) 621-0134
- Telephone the NASA Access Help Desk at (301) 621-0390
- Write to:
 NASA Access Help Desk
 NASA Center for AeroSpace Information
 7121 Standard Drive

Hanover, MD 21076-1320

NASA/TM-2000-209891, Vol. 14



Technical Report Series on the Boreal Ecosystem-Atmosphere Study (BOREAS)

Forrest G. Hall and Jeffrey A. Newcomer, Editors

Volume 14 BOREAS AFM-06 Mean Wind Profile Data

James Wilczak, National Oceanic and Atmospheric Administration Environment Technology Laboratory

National Aeronautics and Space Administration

Goddard Space Flight Center Greenbelt, Maryland 20771

	Available from:	
NIAGA Conton for A G T C		Ni-diamater distribution of the control of the cont
NASA Center for AeroSpace Information		National Technical Information Service
7121 Standard Drive		5285 Port Royal Road
Hanover, MD 21076-1320		Springfield, VA 22161
Drice Code: A17		Del - C 1 - A 10
Price Code: A17		Price Code: A10

BOREAS AFM-6 Mean Wind Profile Data

James Wilczak

Summary

The BOREAS AFM-6 team from the NOAA/ETL operated a 915-MHz wind/Radio Acoustic Sounding System (RASS) profiler system in the SSA near the OJP tower from 21-May-1994 to 20-Sep-1994. The data set provides wind profiles at 38 heights, containing the variables of wind speed; wind direction; and the u-, v-, and w-components of the total wind. The data are stored in tabular ASCII files.

Table of Contents

- 1) Data Set Overview
- 2) Investigator(s)
- 3) Theory of Measurements
- 4) Equipment
- 5) Data Acquisition Methods
- 6) Observations
- 7) Data Description
- 8) Data Organization
- 9) Data Manipulations
- 10) Errors
- 11) Notes
- 12) Application of the Data Set
- 13) Future Modifications and Plans
- 14) Software
- 15) Data Access
- 16) Output Products and Availability
- 17) References
- 18) Glossary of Terms
- 19) List of Acronyms
- 20) Document Information

1. Data Set Overview

1.1 Data Set Identification

BOREAS AFM-06 Mean Wind Profile Data

1.2 Data Set Introduction

The data were collected by BOReal Ecosystem-Atmospheric Study (BOREAS) Airborne Fluxes and Meteorology (AFM)-06 team during 5 months covering late spring and summer in 1994. The wind profiler data were measured by the National Oceanic and Atmospheric Administration (NOAA)/Environment Technology Laboratory (ETL) 915-MHz wind/Radio Acoustic Sounding System (RASS) profiler. The data were collected near the Southern Study Area (SSA)-Old Jack Pine (OJP) tower.

1.3 Objective/Purpose

The BOREAS field work objectives were to measure continuous hourly profiles of wind velocity and temperature in the atmospheric boundary layer (ABL) and lower troposphere, to measure the depth of the daytime convective boundary layer, and to measure the occurrence of precipitation, all using a

915-MHz radar wind/RASS profiler. The data were then to be used to document average boundary layer structure, and especially changes in boundary layer structure during the course of the boreal summer growing season.

1.4 Summary of Parameters

The AFM-06 wind profile data set includes vertical profiles of wind velocity and u-, v-, w-components of the wind.

1.5 Discussion

NOAA/ETL operated a 915-MHz wind profiling radar and surface meteorological station near the OJP site in the BOREAS SSA. These instruments ran continuously from 21-May-1994 through 20-Sep-1994.

The data provided by the wind profiler are vertical profiles of wind speed and direction and virtual temperature, as well as boundary layer depth (Zi) and the presence of precipitation. These measurements were made with 100-m vertical resolution with the lowest measurement height at 150 m above ground level (AGL). The maximum height sampled was 3850 m AGL, although on many days the maximum height of the wind measurements was in the range of 2-3 km due to weak signal strength in the region of the lower troposphere above the ABL.

1.6 Related Data Sets

BOREAS AFM-06 Mean Temperature Profile Data BOREAS AFM-06 Boundary Layer Height Data BOREAS AFM-06 Surface Meteorological Data

2. Investigator(s)

2.1 Investigator(s) Name and Title

Robert Banta, Brooks Martner, James Wilczak NOAA Environmental Laboratory

2.2 Title of Investigation

Outer Boundary Layer Effects on Surface Fluxes of Momentum, Heat, Moisture, and Greenhouse Gases from the Boreal Forest

2.3 Contact Information

Contact 1:

James Wilczak NOAA/ETL 325 Broadway Boulder, CO 80303 (303) 497-6245 jwilczak@etl.noaa.gov

Contact 2:

Jeffrey A. Newcomer Raytheon ITSS Code 923 NASA GSFC Greenbelt, MD 20771 (301) 286-7858 (301) 286-0239 (fax) Jeffrey.Newcomer@gsfc.nasa.gov

3. Theory of Measurements

The above measurements were obtained by measuring the zeroth, first, and second moments of the radar Doppler spectrum. The zeroth moment is the signal power. The range-corrected signal power can alternatively be expressed in terms of the turbulence structure parameter CN2. It is well-known that the vertical profile of CN2 exhibits a sharp peak at the midpoint of the inversion transition region, due to local mixing of relatively cool, moist boundary layer air with warmer and dryer air aloft. Our measurements of Zi were obtained from the peak value in the vertical profile of CN2 from a vertically pointing radar beam. The first moment of the Doppler spectrum is the Doppler velocity. The vertical profile of wind velocity was measured by combining the Doppler velocities measured along three radar beams: one vertical, and two oblique beams pointing at elevations of 75 degrees, oriented 90 degrees apart. The vertical profile of virtual temperature was measured using the RASS, in which an array of acoustic speakers surrounds the radar and generates a sound pulse. The radar signal reflects off of this acoustic wave front, and the measured Doppler shift indicates the velocity of the sound pulse, which is proportional to the virtual temperature of the air. The second moment of the Doppler spectrum, or spectral width, can provide a measure of the strength of the turbulence within the boundary layer. The second moment has not been directly used in the present analysis. Finally, the presence of precipitation is determined by using both signal power and the vertical velocity. Rain and snow have much greater signal power than does clear air, and nearly uniform downward velocities. Rain can be distinguished from snow by its greater reflectivity, and by its greater fall velocity. Because of the high sensitivity of the profiler, it is capable of detecting small amounts of rain that might not be measured by a traditional surface rain gauge. The profiler detects only the presence of precipitation, however, and at present cannot give a quantitative measure of rainfall amount.

4. Equipment

4.1 Sensor/Instrument Description

915-MHz wind profiling radar with RASS.

4.1.1 Collection Environment

The 915-MHz profiler was used during various ambient weather conditions that occurred at the BOREAS SSA-OJP site.

4.1.2 Source/Platform

Ground-based.

4.1.3 Source/Platform Mission Objectives

The ground supported the needed instrumentation.

4.1.4 Key Variables

Included in this data set are wind profiles at 38 heights, containing the variables of wind speed; wind direction; and the u-, v-, and w-components of the total wind.

4.1.5 Principles of Operation

Standard Doppler radar techniques.

4.1.6 Sensor/Instrument Measurement Geometry

One vertical beam, two oblique beams 15 degrees from vertical at an elevation of 75 degrees.

4.1.7 Manufacturer of Sensor/Instrument

Wind Profiler: NOAA/ETL (Contact: James Wilczak at the address found in Section 2).

4.2 Calibration

4.2.1 Specifications

None given.

4.2.1.1 Tolerance

None given.

4.2.2 Frequency of Calibration

None given.

4.2.3 Other Calibration Information

None given.

5. Data Acquisition Methods

During the course of 1 hour, the radar makes 18 cycles through each of the three radial beams, averaging for 60 seconds on each beam. These measurements require a total of 54 minutes. Prior to this, the RASS temperature profile is measured on the vertical beam during the first 5 minutes of the hour. During BOREAS, the RASS temperature observations consisted of 15 measurements, each 15 seconds in length. Each of these individual radial measurements of both wind and temperature is then quality controlled through an automated pattern recognition scheme, and then the measurements are combined into a single value of wind and temperature reported for each hour.

6. Observations

6.1 Data Notes

The wind profiler operated unattended for most of the 4-month observation period.

6.2 Field Notes

The wind profiling radar and surface meteorological stations were located at a site 1.0 km south and 1.6 km east of the SSA-OJP tower flux site. The radar site was in a clearing in the jack pine forest, with fetches (clear distances) of 200 m to the north, 500 m to the south, 150 m to the east, and 1 km to the west. Ground cover within the clearing consisted of grass, brush, and young jack pine trees, approximately 1-2 m tall.

7. Data Description

7.1 Spatial Characteristics

7.1.1 Spatial Coverage

The North American Datum of 1983 (NAD83) coordinates of the site are:

Lat. = $53.91 \, ^{\circ}N$ Long. = $104.40 \, ^{\circ}W$

Alt. = 511 m above sea level

This is located 1.0 km south and 1.6 km east of the SSA-OJP flux tower.

7.1.2 Spatial Coverage Map

Not applicable.

7.1.3 Spatial Resolution

```
Beamwidth = 9.9 degrees (one-way, 3 dB)
Range resolution = 101 m
Range limits = 0.112-3.889 km AGL (38 range gates)
```

7.1.4 Projection

Not applicable.

7.1.5 Grid Description

Not applicable.

7.2 Temporal Characteristics

7.2.1 Temporal Coverage

Measurements were made from 21-May-1994 through 20-Sep-1994.

7.2.2 Temporal Coverage Map

Not available.

7.2.3 Temporal Resolution

Measurements were made 15 times per hour during the period.

7.3 Data Characteristics

7.3.1 Parameter/Variable

The parameters contained in the data files on the CD-ROM are:

Column Name ______ SITE NAME SUB_SITE DATE_OBS TIME_OBS HT_ASL WIND_SPEED WIND_DIR U_COMPNT V_COMPNT W_COMPNT POINTS_OBLIQUE_BEAM_1 SNR_OBLIQUE_BEAM_1 POINTS_OBLIQUE_BEAM_2 SNR_OBLIQUE_BEAM_2 POINTS_VERTICAL_BEAM SNR_VERTICAL_BEAM NUM_LVLS QUAL_CONTROL CRTFCN_CODE REVISION_DATE

7.3.2 Variable Description/DefinitionThe descriptions of the parameters contained in the data files on the CD-ROM are:

Column Name	Description
SITE_NAME	The identifier assigned to the site by BOREAS, in the format SSS-TTT-CCCCC, where SSS identifies the portion of the study area: NSA, SSA, REG, TRN, and TTT identifies the cover type for the site, 999 if unknown, and CCCCC is the identifier for site, exactly what it means will vary with site type.
SUB_SITE	The identifier assigned to the sub-site by BOREAS in the format GGGGG-IIIII, where GGGGG is the group associated with the sub-site instrument, e.g. HYD06 or STAFF, and IIIII is the identifier for sub-site, often this will refer to an instrument.
DATE_OBS	The date on which the data were collected.
TIME_OBS	The Greenwich Mean Time (GMT) when the data were collected.
HT_ASL	The height above mean sea level at which the measurements were taken.
WIND_SPEED	The wind speed.
WIND_DIR	The direction from which the wind was traveling, increasing in a clockwise direction from north.
U_COMPNT	The measured u-component of the total wind velocity
V_COMPNT	The measure v-component of the total wind velocity.
W_COMPNT	The measured w-component of the total wind velocity
POINTS_OBLIQUE_BEAM_1	The number of points in oblique beam #1.
SNR_OBLIQUE_BEAM_1	The signal to noise ratio for oblique beam #1.
POINTS_OBLIQUE_BEAM_2	The number of points in oblique beam #2.
SNR_OBLIQUE_BEAM_2	The signal to noise ratio for oblique beam #2.
POINTS_VERTICAL_BEAM	The number of points in the vertical beam.
SNR_VERTICAL_BEAM NUM_LVLS	The signal to noise ratio of the vertical beam. The number of height levels in the atmospheric
QUAL_CONTROL	profile. A quality control parameter. A value of 0 or 1 can be considered good. A value of 7 or 8 indicates suspect or bad data. QC Code Definition: 0 Valid 1 Estimated 7 Suspect
CRTFCN_CODE	8 Invalid The BOREAS certification level of the data. Examples are CPI (Checked by PI), CGR (Certified by Group), PRE (Preliminary), and CPI-??? (CPI but questionable).
REVISION_DATE	The most recent date when the information in the referenced data base table record was revised.

For the columns WIND_SPEED, POINTS_OBLIQUE_BEAM_1, SNR_OBLIQUE_BEAM_1, POINTS_OBLIQUE_BEAM_2, SNR_OBLIQUE_BEAM_2, POINTS_VERTICAL_BEAM, SNR_VERTICAL_BEAM the following data definitions apply:

```
Data Code Definition: -940 --- Failed QC,
-950 --- Failed Consensus
-960 --- Exceeded Nyquist Vel.
-980 --- Flagged by Reviewer
-999 --- Missing or Not Reported.
```

7.3.3 Unit of Measurement

The measurement units for the parameters contained in the data files on the CD-ROM are:

Column Name	Units
SITE_NAME	[none]
SUB_SITE	[none]
DATE_OBS	[DD-MON-YY]
TIME_OBS	[HHMM GMT]
HT_ASL	[meters]
WIND_SPEED	[meters][second^-1]
WIND_DIR	[degrees]
U_COMPNT	[meters][second^-1]
V_COMPNT	[meters][second^-1]
W_COMPNT	[meters][second^-1]
POINTS_OBLIQUE_BEAM_1	[counts]
SNR_OBLIQUE_BEAM_1	[unitless]
POINTS_OBLIQUE_BEAM_2	[counts]
SNR_OBLIQUE_BEAM_2	[unitless]
POINTS_VERTICAL_BEAM	[counts]
SNR_VERTICAL_BEAM	[unitless]
NUM_LVLS	[unitless]
QUAL_CONTROL	[unitless]
CRTFCN_CODE	[none]
REVISION_DATE	[DD-MON-YY]

7.3.4 Data Source

The sources of the parameter values contained in the data files on the CD-ROM are:

Column Name	Data Source
SITE_NAME	[Assigned by BORIS]
SUB_SITE	[Assigned by BORIS]
DATE_OBS	[Supplied by NOAA/ETL]
TIME_OBS	[Supplied by NOAA/ETL]
HT_ASL	[Supplied by NOAA/ETL]
WIND_SPEED	[Supplied by NOAA/ETL]
WIND_DIR	[Supplied by NOAA/ETL]
U_COMPNT	[Supplied by NOAA/ETL]
V_COMPNT	[Supplied by NOAA/ETL]
W_COMPNT	[Supplied by NOAA/ETL]
POINTS_OBLIQUE_BEAM_1	[Supplied by NOAA/ETL]
SNR_OBLIQUE_BEAM_1	[Supplied by NOAA/ETL]
POINTS_OBLIQUE_BEAM_2	[Supplied by NOAA/ETL]

SNR_OBLIQUE_BEAM_2	[Supplied	by	NOAA/ETL]
POINTS_VERTICAL_BEAM	[Supplied	by	NOAA/ETL]
SNR_VERTICAL_BEAM	[Supplied	by	NOAA/ETL]
NUM_LVLS	[Supplied	by	NOAA/ETL]
QUAL_CONTROL	[Supplied	by	NOAA/ETL]
CRTFCN_CODE	[Assigned	by	BORIS]
REVISION_DATE	[Assigned	by	BORIS]

7.3.5 Data Range

The following table gives information about the parameter values found in the data files on the CD-ROM.

	Minimum Data	Maximum	Missng Data		Below	Data Not
G 1 17		Data			Detect	
Column Name		Value	value	value	Limit	Cllctd
SITE_NAME	SSA-OJP-RDR01	SSA-OJP-RDR01	None	None	None	None
SUB_SITE	AFM06-RDR01	AFM06-RDR01	None	None	None	None
DATE_OBS	21-MAY-94	21-SEP-94	None	None	None	None
TIME_OBS	0	2300	None	None	None	None
HT_ASL	663	4400	None	None	None	None
WIND_SPEED	-980	58.8	None	None	None	None
WIND_DIR	-980	360	None	None	None	None
U_COMPNT	-17.31	26.98	-999	None	None	None
V_COMPNT	-23.9	23.89	-999	None	None	None
W_COMPNT	-10.9	10.82	-999	None	None	None
POINTS_OBLIQUE_BEAM_	-950	19	None	None	None	None
1						
SNR_OBLIQUE_BEAM_1	-950	79	None	None	None	None
POINTS_OBLIQUE_BEAM_	-950	19	None	None	None	None
2						
SNR_OBLIQUE_BEAM_2	-950	155	None	None	None	None
POINTS_VERTICAL_BEAM	-950	19	None	None	None	None
SNR_VERTICAL_BEAM	-950	56	None	None	None	None
NUM_LVLS	38	38	None	None	None	None
QUAL_CONTROL	0	8	None	None	None	None
CRTFCN_CODE	CPI	CPI	None	None	None	None
REVISION_DATE	21-AUG-96	22-AUG-96	None	None	None	None

Minimum Data Value -- The minimum value found in the column.

Maximum Data Value -- The maximum value found in the column.

Missng Data Value -- The value that indicates missing data. This is used to indicate that an attempt was made to determine the parameter value, but the attempt was unsuccessful.

Unrel Data Value -- The value that indicates unreliable data. This is used to indicate an attempt was made to determine the

parameter value, but the value was deemed to be

unreliable by the analysis personnel.

Below Detect Limit -- The value that indicates parameter values below the instruments detection limits. This is used to indicate that an attempt was made to determine the parameter value, but the analysis personnel determined that the parameter value was below the detection limit of the instrumentation.

Data Not Cllctd

-- This value indicates that no attempt was made to determine the parameter value. This usually indicates that BORIS combined several similar but not identical data sets into the same data base table but this particular science team did not measure that parameter.

Blank -- Indicates that blank spaces are used to denote that type of value. N/A -- Indicates that the value is not applicable to the respective column. None -- Indicates that no values of that sort were found in the column.

7.4 Sample Data Record

The following is a wrapped version of a data record from a sample data file on the CD-ROM.

```
SITE_NAME, SUB_SITE, DATE_OBS, TIME_OBS, HT_ASL, WIND_SPEED, WIND_DIR, U_COMPNT, V_COMPNT, W_COMPNT, POINTS_OBLIQUE_BEAM_1, SNR_OBLIQUE_BEAM_1, POINTS_OBLIQUE_BEAM_2, SNR_OBLIQUE_BEAM_2, POINTS_VERTICAL_BEAM, SNR_VERTICAL_BEAM, NUM_LVLS, QUAL_CONTROL, CRTFCN_CODE, REVISION_DATE
'SSA-OJP-RDR01', 'AFM06-RDR01', 23-JUN-94, 0, 663, 5.4, 245, 4.89, 2.27, .09, 18, 7, -18, 12, 18, 10, 38, 1, 'CPI', 22-AUG-96
'SSA-OJP-RDR01', 'AFM06-RDR01', 23-JUN-94, 0, 764, 4.8, 248, 4.47, 1.77, .03, 18, 10, -18, 15, 18, 12, 38, 1, 'CPI', 22-AUG-96
'SSA-OJP-RDR01', 'AFM06-RDR01', 23-JUN-94, 0, 966, 4.5, 251, 4.26, 1.47, -.05, 18, 10, 18, 14, 18, 11, 38, 0, 'CPI', 22-AUG-96
```

8. Data Organization

8.1 Data Granularity

The smallest unit of data tracked by the BOREAS Information System (BORIS) was the data collected at a given site on a given date.

8.2 Data Format(s)

The Compact Disk-Read-Only Memory (CD-ROM) files contain American Standard Code for Information Interchange (ASCII) numerical and character fields of varying length separated by commas. The character fields are enclosed with single apostrophe marks. There are no spaces between the fields.

Each data file on the CD-ROM has four header lines of Hyper-Text Markup Language (HTML) code at the top. When viewed with a Web browser, this code displays header information (data set title, location, date, acknowledgments, etc.) and a series of HTML links to associated data files and related data sets. Line 5 of each data file is a list of the column names, and line 6 and following lines contain the actual data.

9. Data Manipulations

9.1 Formulae

9.1.1 Derivation Techniques and Algorithms

None given.

9.2 Data Processing Sequence

9.2.1 Processing Steps

During the course of 1 hour, the radar makes 18 cycles through each of the three radial beams, averaging for 60 seconds on each beam. These measurements require a total of 54 minutes. Prior to this, the RASS temperature profile is measured on the vertical beam during the first 5 minutes of the hour. During BOREAS, the RASS temperature observations consisted of 15 measurements, each 15 seconds in length. Each of these individual radial measurements of both wind and temperature is then quality controlled through an automated pattern recognition scheme, and then the measurements are combined into a single value of wind and temperature reported for each hour.

9.2.2 Processing Changes

None given.

9.3 Calculations

9.3.1 Special Corrections/Adjustments

None given.

9.3.2 Calculated Variables

None given.

9.4 Graphs and Plots

None given.

10. Errors

10.1 Sources of Error

During spring and autumn seasons, it is possible that the profiler winds can be contaminated by the presence of migrating birds. These errors are now well understood, and can be recognized from large values of signal power, spectral width, and sudden changes in wind speed occurring near sunset and sunrise. Periods of contaminated winds have been hand edited from the data set. Birds do not directly affect RASS temperatures, although they could have a secondary effect by contaminating vertical velocity, which is used to correct RASS temperatures. No corrections for contaminated vertical velocities on RASS have been made.

10.2 Quality Assessment

10.2.1 Data Validation by Source

See Section 10.2.3.

10.2.2 Confidence Level/Accuracy Judgment

See Section 10.2.3.

10.2.3 Measurement Error for Parameters

During the first 3 days and last 3 days of operation, ETL personnel were at the site taking balloon intercomparisons. These assessments have shown typical values of agreement of the balloons with profiler, typically 1-2 m/s and 1 deg C. Wind velocity differences between 915-MHz wind profilers and precision research aircraft have been found to be on the order of 0.9 m/s.

10.2.4 Additional Quality Assessments

None given.

10.2.5 Data Verification by Data Center

BORIS personnel verified that the delivered data agreed with the information provided by the AFM-06 team.

11. Notes

11.1 Limitations of the Data

None given.

11.2 Known Problems with the Data

None given.

11.3 Usage Guidance

None given.

11.4 Other Relevant Information

None given.

12. Application of the Data Set

These data would be used to study and model wind motion at various levels of the atmosphere above the site.

13. Future Modifications and Plans

None given.

14. Software

14.1 Software Description

None given.

14.2 Software Access

None given.

15. Data Access

The mean wind profile data are available from the Earth Observing System Data and Information System (EOSDIS) Oak Ridge National Laboratory (ORNL) Distributed Active Archive Center (DAAC).

15.1 Contact Information

For BOREAS data and documentation please contact:

ORNL DAAC User Services Oak Ridge National Laboratory P.O. Box 2008 MS-6407 Oak Ridge, TN 37831-6407 Phone: (423) 241-3952

Fax: (423) 574-4665

E-mail: ornldaac@ornl.gov or ornl@eos.nasa.gov

15.2 Data Center Identification

Earth Observing System Data and Information System (EOSDIS) Oak Ridge National Laboratory (ORNL) Distributed Active Archive Center (DAAC) for Biogeochemical Dynamics http://www-eosdis.ornl.gov/ [Internet Link].

15.3 Procedures for Obtaining Data

Users may obtain data directly through the ORNL DAAC online search and order system [http://www-eosdis.ornl.gov/] and the anonymous FTP site [ftp://www-eosdis.ornl.gov/data/] or by contacting User Services by electronic mail, telephone, fax, letter, or personal visit using the contact information in Section 15.1.

15.4 Data Center Status/Plans

The ORNL DAAC is the primary source for BOREAS field measurement, image, GIS, and hardcopy data products. The BOREAS CD-ROM and data referenced or listed in inventories on the CD-ROM are available from the ORNL DAAC.

16. Output Products and Availability

16.1 Tape Products

None.

16.2 Film Products

None.

16.3 Other Products

These data are available on the BOREAS CD-ROM series.

17. References

17.1 Platform/Sensor/Instrument/Data Processing Documentation

Angevine, W.M. and J.I. MacPherson. 1995. Comparison of wind profiler and aircraft wind measurements at Chebogue Point, Nova Scotia. J. Atmos. Ocean. Technol. 12(2), 421 426.

Angevine, W.M. and W.L. Ecklund. 1994. Errors in radio acoustic sounding of temperature. J. Atmos. Ocean. Technol. 11, 42 49.

Gage, K.S., C.R. Williams, and W.L. Ecklund. 1994. UHF wind profilers: A new tool for diagnosing tropical convective cloud systems. Bull. Amer. Meteor. Soc. 75, 2289 2294.

Gossard, E.E. and R.G. Strauch. 1983. Radar observations of clear air and clouds. Elsevier, Amsterdam, 280 pp.

May, P.T., K.P. Moran, and R.G. Strauch. 1989. The accuracy of RASS temperature measurements. J. Appl. Meteor. 28, 1329 1335.

Moran, K.P. and R.G. Strauch. 1994. The accuracy of RASS temperature measurements corrected for vertical air motion. J. Atmos. Ocean. Technol. 11, 995 1001.

Peters, G. 1994. Correction of turbulence induced errors of RASS temperature profiles. Proc., 3rd Intl Symp. on Tropospheric Profiling: Needs and Technologies, Hamburg, Max Planck-Gesellschaft zur Förderung der Wissenschaften, pp. 266 268.

17.2 Journal Articles and Study Reports

Angevine, W.M., A.B. White, and S.K. Avery. 1994b. Boundary-layer depth and entrainment zone characterization with a boundary-layer profiler. Boundary-Layer Meteorol. 68, 375 385.

May, P.T. and J.M. Wilczak. 1993. Diurnal and seasonal variations of boundary layer structure observed with a radar wind profiler and RASS. Mon. Wea. Rev. 121, 673 682.

Merritt, D.A. 1995. A statistical averaging method for wind profiler Doppler spectra. J. Atmos. Ocean. Technol. (accepted for publication).

Newcomer, J., D. Landis, S. Conrad, S. Curd, K. Huemmrich, D. Knapp, A. Morrell, J. Nickeson, A. Papagno, D. Rinker, R. Strub, T. Twine, F. Hall, and P. Sellers, eds. 2000. Collected Data of The Boreal Ecosystem-Atmosphere Study. NASA. CD-ROM.

Ralph, F.M. 1995. Using radar-measured radial vertical velocities to distinguish precipitation scattering from clear-air scattering, J. Atmos. Ocean. Technol. 12, 257 267.

Rogers, R.R., W.L. Ecklund, D.A. Carter, K.S. Gage, and S.A. Ethier. 1993. Research applications of a boundary-layer wind profiler, Bull. Amer. Meteor. Soc. 74, 567 580.

Sellers, P. and F. Hall. 1994. Boreal Ecosystem-Atmosphere Study: Experiment Plan. Version 1994-3.0, NASA BOREAS Report (EXPLAN 94).

Sellers, P. and F. Hall. 1996. Boreal Ecosystem-Atmosphere Study: Experiment Plan. Version 1996-2.0, NASA BOREAS Report (EXPLAN 96).

Sellers, P., F. Hall, and K.F. Huemmrich. 1996. Boreal Ecosystem-Atmosphere Study: 1994 Operations. NASA BOREAS Report (OPS DOC 94).

Sellers, P., F. Hall, and K.F. Huemmrich. 1997. Boreal Ecosystem-Atmosphere Study: 1996 Operations. NASA BOREAS Report (OPS DOC 96).

Sellers, P., F. Hall, H. Margolis, B. Kelly, D. Baldocchi, G. den Hartog, J. Cihlar, M.G. Ryan, B. Goodison, P. Crill, K.J. Ranson, D. Lettenmaier, and D.E. Wickland. 1995. The boreal ecosystem-atmosphere study (BOREAS): an overview and early results from the 1994 field year. Bulletin of the American Meteorological Society. 76(9):1549-1577.

Sellers, P.J., F.G. Hall, R.D. Kelly, A. Black, D. Baldocchi, J. Berry, M. Ryan, K.J. Ranson, P.M. Crill, D.P. Lettenmaier, H. Margolis, J. Cihlar, J. Newcomer, D. Fitzjarrald, P.G. Jarvis, S.T. Gower, D. Halliwell, D. Williams, B. Goodison, D.E. Wickland, and F.E. Guertin. 1997. BOREAS in 1997: Experiment Overview, Scientific Results and Future Directions. Journal of Geophysical Research 102(D24): 28,731-28,770.

Whiteman, C.D. and X. Bian. 1994. Semidiurnal solar tides in the mountain atmosphere, Proc., 23rd Conf. on Alpine Meteorology (Lindau, Germany), Deutsche Wetterdienst, Offenbach, Germany.

Wilczak, J.M., R.G. Strauch, F.M. Ralph, B.L. Weber, D.A. Merritt, J.R. Jordan, D.E. Wolfe, L.K. Lewis, D.B. Wuertz, J.E. Gaynor, S.A. McLaughlin, R.R. Rogers, A.C. Riddle, and T.S. Dye. 1995. Contamination of wind profiler data by migrating birds: Characteristics of corrupted data and potential solutions. J. Atmos. Ocean. Technol. 12, 449 467.

17.3 Archive/DBMS Usage Documentation None.

18. Glossary of Terms

None given.

19. List of Acronyms

 ABL - Atmospheric Boundary Layer AFM - Airborne Fluxes and Meteorology ASCII - American Standard Code for Information Interchange BOREAS - BOReal Ecosystem-Atmosphere Study - BOREAS Information System BORIS CD-ROM - Compact Disk - Read Only Memory DAAC - Distributed Active Archive Center EOS - Earth Observing System EOSDIS - EOS Data and Information System ETL - Environment Technology Laboratory GIS - Geographic Information System GMT - Greenwich Mean Time GSFC - Goddard Space Flight Center NAD83 - North American Data of 1983 NASA - National Aeronautics and Space Administration - National Oceanic and Atmospheric Administration NOAA NSA - Northern Study Area OJP - Old Jack Pine ORNL - Oak Ridge National Laboratory - Prince Albert National Park PANP

RASS - Radio Acoustic Sounding System

SSA - Southern Study Area

URL - Uniform Resource Locator

20. Document Information

20.1 Document Revision Dates

Written: 07-Jun-1996 Last Updated: 27-Aug-1999

20.2 Document Review Dates

BORIS Review: 29-Jan-1999

Science Review:

20.3 Document ID

20.4 Citation

When using these data, please include the following acknowledgment as well as citations of relevant papers in Section 17.2:

Wind profiler (and/or surface meteorological) data provided by Dr. James Wilczak, NOAA Environmental Technology Laboratory

If using data from the BOREAS CD-ROM series, also reference the data as:

Banta, R., B. Martner, and J. Wilczak, "Outer Boundary Layer Effects on Surface Fluxes of Momentum, Heat, Moisture, and Greenhouse Gases from the Boreal Forest." In Collected Data of The Boreal Ecosystem-Atmosphere Study. Eds. J. Newcomer, D. Landis, S. Conrad, S. Curd, K. Huemmrich, D. Knapp, A. Morrell, J. Nickeson, A. Papagno, D. Rinker, R. Strub, T. Twine, F. Hall, and P. Sellers. CD-ROM. NASA, 2000.

Also, cite the BOREAS CD-ROM set as:

Newcomer, J., D. Landis, S. Conrad, S. Curd, K. Huemmrich, D. Knapp, A. Morrell, J. Nickeson, A. Papagno, D. Rinker, R. Strub, T. Twine, F. Hall, and P. Sellers, eds. Collected Data of The Boreal Ecosystem-Atmosphere Study. NASA. CD-ROM. NASA, 2000.

20.5 Document Curator

20.6 Document URL

REPORT DOCUMENTATION PAGE

Form Approved OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

4 4 6 5 1 6 V 1 6 5 6 1 1 V (1	La DEDADE DATE		D D 1 TEO 001/FD ED
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE June 2000	3. REPORT TYPE AND DATES COVERED Technical Memorandum	
	June 2000	Technical M	
4. TITLE AND SUBTITLE			5. FUNDING NUMBERS
Technical Report Series on the Bo	oreal Ecosystem-Atmosphere	e Study (BOREAS)	
BOREAS AMF-06 Mean Win	nd Profile Data		923
C AUTHOR(C)			RTOP: 923-462-33-01
6. AUTHOR(S)			111 011 920 102 00 01
James Wilczak			
Forrest G. Hall and Jeffrey A	. Newcomer, Editors		
7. PERFORMING ORGANIZATION NAMI	E(S) AND ADDRESS (ES)		8. PEFORMING ORGANIZATION REPORT NUMBER
Goddard Space Flight Center			REPORT NUMBER
Greenbelt, Maryland 20771			2000-03136-0
Greenbert, iviary land 20771			2000 03130 0
9. SPONSORING / MONITORING AGE	ENCY NAME(S) AND ADDRESS	S (ES)	10. SPONSORING / MONITORING
			AGENCY REPORT NUMBER
National Aeronautics and Space	e Administration		TM-2000-209891
Washington, DC 20546-0001			Vol. 14
11. SUPPLEMENTARY NOTES			
J. Wilczak: National Oceanic	and Atmospheric Admin	istration Environm	ent Technology Laboratory:
Jeffrey A. Newcomer: Raythe	-	istration Environn	ient reenhology Laboratory,
Jenney A. Newconner. Rayund	7011 11 33		
12a. DISTRIBUTION / AVAILABILITY STA	ATEMENT		12b. DISTRIBUTION CODE
Unclassified–Unlimited			
Subject Category: 43			
Report available from the NASA	A Center for AeroSpace Inf	ormation,	
7121 Standard Drive, Hanover,	MD 21076-1320. (301) 62	1-0390.	
13. ABSTRACT (Maximum 200 words)			

The BOREAS AFM-6 team from the NOAA/ETL operated a 915-MHz wind/Radio Acoustic Sounding System (RASS) profiler system in the SSA near the OJP tower from 21-May-1994 to 20-Sep-1994. The data set provides wind profiles at 38 heights, containing the variables of wind speed; wind direction; and the u-, v-, and w-components of the total wind. The data are stored in tabular ASCII files.

14. SUBJECT TERMS BOREAS, wind speed, w	15. NUMBER OF PAGES 15 16. PRICE CODE		
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT UL